

Xitech's Multi-Well Controllers

8 Skimmer Controller

The **5000ES Programmable Controller** provides individual intermittent control for 8 Skimmers through an internal solenoid assembly. Air supply is distributed from the **5000ES** out to the Skimmers in the well field. The **5000ES** provides individual logging of each Skimmer's elapsed operating time,

continuous fault monitoring of the high tank shutoff sensor, manual control over all 8 stations, battery backed program memory, and includes a high tank shutoff assembly.



Model 5000ES Controller

Pumping times: 1 - 99 minutes

Pumping cycles per day: 1 - 99 cycles

Pumping cycles beyond a day: 1 - 99 days

8 individual control stations

Programmable intermittent control

Digital recording of elapsed pumping time

Battery backed program memory

Visual indicator displays tank full condition

Power: 12 volt DC & 110 AC or 12 volt DC & 220 AC

Maximum air pressure: 125 PSI

Size: 12 inches x 14 inches x 6 inches

NEMA 4 enclosure

Weight: 25 pounds

16 Skimmer Controller

The **5500ES Programmable Controller** provides individual intermittent control for 16 Skimmers through internal solenoid assemblies. Air supply is distributed from the **5500ES** out to the Skimmers in the well field. The **5500ES** provides

individual logging of each Skimmer's elapsed operating time, continuous fault monitoring of the high tank shutoff switch, manual control over all 16 stations, battery backed program memory, and includes a high tank shutoff assembly.

Model 5500ES Controller

Pumping times: 1 - 99 minutes

Pumping cycles per day: 1 - 99 cycles

Pumping cycles beyond a day: 1 - 99 days

16 individual control stations

Programmable intermittent control

Digital recording of elapsed pumping time

Battery-backed program memory

Visual indicator displays tank full condition

Power: 110 AC or 220 AC

Maximum air pressure: 125 PSI

Size: 12 inches x 14 inches x 6 inches

NEMA 4 enclosure

Weight: 29 pounds



toll free
888-867-9483

www.xitechinc.com